

Lecture # 2.1

Engineering Materials

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

1

1

Engineering Materials

Introduction

It is necessary to choose a suitable material for use in machine element,

and the Choice of material depends very much on its properties, cost, availability and such other factors.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

2

2

Engineering Materials

Common Engineering materials are normally classified as Metals and non-Metals.

Metals may conveniently be divided into ferrous and non-ferrous metals.

Important ferrous metals for the design purpose are:

- (i) cast iron
- (ii) wrought iron
- (iii) steel.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

3

3

Engineering Materials

Some of the important non-ferrous metals used in engineering design are:

- (a) Light metal group such as Aluminium and its alloys, Magnesium and Manganese alloys.
- (b) Copper based alloys such as brass (Cu-Zn), bronze (Cu-Sn).
- (c) White metal group such as Nickel, Silver, White Bearing Metals eg. SnSb7Cu3, Sn60Sb11Pb, Zinc etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

4

4

Engineering Materials

Ferrous Materials

(i) Cast iron -

It is an alloy of iron, carbon and silicon

it is hard and brittle.

Carbon content may be within 1.7% to 3%

carbon may be present as free carbon or iron carbide Fe_3C .

The Cast Iron is further categorized as:

(a) Grey cast iron

(b) White cast iron

(c) Malleable cast iron

(d) Spheroidal or nodular cast iron

(e) Austenitic cast iron

(f) Abrasion resistant cast iron.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

5

5

Engineering Materials

(a) Grey cast iron -

Carbon is present in the form of graphite.

This type of cast iron is inexpensive

It has high compressive strength.

Graphite is an excellent solid lubricant, and this makes it easily machinable but brittle.

Some examples of this type of cast iron are FG20, FG35 or FG35Si15.

The numbers indicate ultimate tensile strength in MPa and 15 indicates 0.15% silicon.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

6

6

Engineering Materials

(b) White cast iron -

In these carbon is present in the form of iron carbide (Fe_3C) which is hard and brittle.

The presence of iron carbide increases hardness and makes it difficult to machine.

Consequently, these cast irons are abrasion resistant.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

7

7

Engineering Materials

(c) Malleable cast iron -

These are white cast irons rendered malleable by annealing.

These are tougher than grey cast iron

They can be twisted or bent without fracture.

They have excellent machining properties

They are inexpensive.

They are used for making parts where forging is expensive such as hubs for wagon wheels, brake supports.

Depending on the method of processing they may be designated as black heart BM32, BM30 or white heart WM42, WM35 etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

8

8

Engineering Materials

(d) Spheroidal or nodular graphite cast iron -

In these cast irons graphite is present in the form of spheres or nodules.

They have high tensile strength

They have good elongation properties.

They are designated as, for example, SG50/7, SG80/2 etc

where the first number gives the tensile strength in Mpa and the second number indicates percentage elongation.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

9

9

Engineering Materials

(e) Austenitic cast iron -

Depending on the form of graphite present these cast iron can be classified broadly under two headings:

Austenitic flake graphite iron designated, for example, AFGNi16Cu7Cr2 and

Austenitic spheroidal or nodular graphite iron designated, for example, ASGNi20Cr2.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

10

10

Engineering Materials

(e) Austenitic cast iron -

These are alloy cast irons, and they contain small percentages of silicon, manganese, sulphur, phosphorus etc.

They may be produced by adding alloying elements viz. nickel, chromium, molybdenum, copper and manganese in sufficient quantities.

These elements give more strength and improved properties.

They are used for making automobile parts such as cylinders, pistons, piston rings, brake drums etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

11

11

Engineering Materials

(f) Abrasion resistant cast iron -

These are alloy cast iron, and the alloying elements render abrasion resistance.

A typical designation is ABR33 Ni4 Cr2 which indicates a tensile strength in kg/mm² with 4% nickel and 2% chromium.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

12

12

Engineering Materials

(ii) Wrought iron -

This is a very pure iron where the iron content is of the order of 99.5%.

It is produced by re-melting pig iron

some small amount of silicon, sulphur, or phosphorus may be present.

It is tough, malleable and ductile and can easily be forged or welded.

It cannot however take sudden shock.

Chains, crane hooks, railway couplings and such other components may be made of this iron.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

13

13

Engineering Materials

(iii) Steel -

This is by far the most important engineering material

and there is an enormous variety of steel to meet the wide variety of engineering requirements.

It is an alloy of iron and carbon in which the carbon content can be less than 1.7%

and carbon is present in the form of iron carbide to impart hardness and strength.

Two main categories of steel are

(a) Plain carbon steel and

(b) alloy steel.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

14

14

Engineering Materials

(a) Plain carbon steel -

The properties of plain carbon steel depend mainly on the carbon percentages

and other alloying elements are not usually present in more than 0.5 to 1% such as 0.5% Si or 1% Mn etc.

There is a large variety of plain carbon steel and they are designated as C01, C14, C45, C70 and so on

where the number indicates the carbon percentage.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

15

15

Engineering Materials

Following are the categorization of plain carbon steels on the basis of carbon percentage:

Dead mild steel - upto 0.15% C

Low carbon steel or mild steel - 0.15 to 0.46% C

Medium carbon steel - 0.45 to 0.8% C.

High carbon steel - 0.8 to 1.5% C

Detailed properties of these steels may be found in any standard handbook but in general higher carbon percentage indicates higher strength.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

16

16

Engineering Materials

(b) Alloy steel -

In order to impart some desired properties, such as wear resistance, corrosion resistance, electric or magnetic properties etc, elements other than carbon are added in sufficient quantities .

The Chief alloying elements added are usually:

Nickel for strength and toughness,

Chromium for hardness and strength,

Tungsten for hardness at elevated temperature,

Vanadium for tensile strength,

Manganese for high strength in hot rolled and heat treated condition,

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

17

17

Engineering Materials

(b) Alloy steel (Continue)-

Silicon for high elastic limit,

Cobalt for hardness and

Molybdenum for extra tensile strength.

Some examples of alloy steels are

35Ni1Cr60,

30Ni4Cr1,

40Cr1Mo28,

37Mn2.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

18

18

Engineering Materials

Stainless steel is one such alloy steel that gives good corrosion resistance.

One important type of stainless steel is often described as 18/8 steel where chromium and nickel percentages are 18 and 8 respectively.

A typical designation of a stainless steel is 15Si2Mn2Cr18Ni8 where carbon percentage is 0.15.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

19

19

Engineering Materials

Specifications of Steels

A number of systems for grading steel exist in different countries.

The American system is usually termed as SAE (Society of Automobile Engineers) or AISI (American Iron and Steel Industries) systems.

In this system the first digit indicates the chief alloying material.

Digits 1,2,3,4 5,6,7and 8 refer to carbon, nickel, nickel/chromium, molybdenum, Chromium, chrome/vanadium, tungsten and Silico/ Manganese respectively.

The second digit or second and third digits give the percentage of main alloying element, and the last two digits indicate the carbon percentage.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

20

20

Engineering Materials

This therefore explains that SAE 71360 indicates an alloy steel with 0.6% carbon and

the percentage of main alloying material tungsten is 13.

In British system steels are designated by the letters En followed by a number such as 1,2...16, 20 etc.

Corresponding constituent elements can be seen from the standards

but in general, En4 is equivalent to C25 steel,

En6 is equivalent to C30 steel and so on.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

21

21

Engineering Materials

Non-Ferrous Metals

Metals containing elements other than iron as their chief constituents are usually referred to as non-ferrous metals.

There is a wide variety of non-metals in practice some are discussed below:

Aluminium -

This is the white metal produced from Alumina.

In its pure state it is weak and soft but addition of small amounts of Cu, Mn, Si and Magnesium makes it hard and strong.

It is also corrosion resistant, low weight and non-toxic.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

22

22

Engineering Materials

Duralumin -

This is an alloy of 4% Cu, 0.5% Mn, 0.5% Mg and Aluminium.

It is widely used in automobile and aircraft components.

Y-alloy -

This is an alloy of 4% Cu, 1.5% Mn, 2% Ni, 6% Si, Mg, Fe and the rest is Al.

It gives large strength at high temperature.

It is used for aircraft engine parts such as cylinder heads, piston etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

23

23

Engineering Materials

Magnalium -

This is an aluminium alloy with 2 to 10 % Magnesium.

It also contains 1.75% Cu.

Due to its light weight and good strength it is used for aircraft and automobile components.

Copper alloys -

Copper is one of the most widely used non-ferrous metals in industry.

It is soft, malleable and ductile and

It is a good conductor of heat and electricity.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

24

24


Engineering Materials

The following two important copper alloys are widely used in practice:

Brass (Cu-Zn alloy) -

It is fundamentally a binary alloy with Zn upto 50% .

As Zn percentage increases, ductility increases upto ~37% of Zn beyond which the ductility falls.



Variation of ductility of brass with percentage of zinc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

25

25

Engineering Materials

Small amount of other elements viz. lead or tin imparts other properties to brass.

Lead gives good machining quality and tin imparts strength.

Brass is highly corrosion resistant, easily machinable and therefore a good bearing material.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

26

26

Engineering Materials

Bronze (Cu-Sn alloy) -

This is mainly a copper-tin alloy where tin percentage may vary between 5 to 25.

It provides hardness but tin content also oxidizes resulting in brittleness.

Deoxidizers such as Zn may be added.

Gun metal is one such alloy where 2% Zn is added as deoxidizing agent and typical compositions are 88% Cu, 10% Sn, 2% Zn.

This is suitable for working in cold state.

It was originally made for casting guns but used now for boiler fittings, bushes, glands and other such uses.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

27

27

Engineering Materials

Non-metals

Non-metallic materials are also used in engineering practice due to their low cost, flexibility and resistance to heat and electricity.

Though there are many suitable non-metals, the following are important few from design point of view:

Timber -

This is a relatively low-cost material and a bad conductor of heat and electricity.

It has also good elastic and frictional properties

It is widely used in foundry patterns and as water lubricated bearings.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

28

28

Engineering Materials

Leather -

This is widely used in engineering for its flexibility and wear resistance.

It is widely used for belt drives, washers and such other applications.

Rubber -

It has high bulk modulus and

is used for drive elements, sealing, vibration isolation and similar applications.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

29

29

Engineering Materials

Plastics -

These are synthetic materials which can be moulded into desired shapes under pressure with or without application of heat.

These are now extensively used in various industrial applications for their corrosion resistance, dimensional stability and relatively low cost.

There are two main types of plastics:

- (a) Thermosetting plastics and
- (b) Thermoplastics

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

30

30

Engineering Materials

(a) Thermosetting plastics -

These plastics are formed under heat and pressure.

It initially softens and with increasing heat and pressure, polymerization takes place.

This results in hardening of the material.

These plastics cannot be deformed or re-moulded again under heat and pressure.

Some examples of thermosetting plastics are

Phenol formaldehyde (Bakelite),

Phenol-furfural (Durite),

Epoxy resins,

Phenolic resins etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

31

31

Engineering Materials

(b) Thermoplastics -

Thermoplastics do not become hard with the application of heat and pressure and no chemical change takes place.

They remain soft at elevated temperatures until they are hardened by cooling.

These can be re-melted and remoulded by application of heat and pressure.

Some examples of thermoplastics are

Cellulose nitrate (celluloid),

Polythene, Polyvinyl Acetate,

Polyvinyl chloride (PVC) etc.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

32

32

Engineering Materials

Mechanical properties of common Engineering Materials

The important properties from design point of view are:

- (a) Elasticity
- (b) Plasticity
- (c) Hardness
- (d) Ductility
- (e) Malleability
- (f) Brittleness
- (g) Resilience
- (h) Toughness
- (i) Creep

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

33

33

Engineering Materials

(a) Elasticity

This is the property of a material to regain its original shape after deformation when the external forces are removed.

All materials are plastic to some extent, but the degree varies,

for example, both mild steel and rubber are elastic materials, but steel is more elastic than rubber.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

34

34

Engineering Materials

(b) Plasticity

This is associated with the permanent deformation of material when the stress level exceeds the yield point.

Under plastic conditions materials ideally deform without any increase in stress.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

35


35

Engineering Materials

A typical stress strain diagram for an elastic-perfectly plastic material is shown in the figure.

Mises-Henky criterion gives a good starting point for plasticity analysis. The criterion is given as

$$(\sigma_1 - \sigma_2)^2 + (\sigma_2 - \sigma_3)^2 + (\sigma_3 - \sigma_1)^2 = 2\sigma_y^2,$$



where σ_1 , σ_2 , σ_3 and σ_y are the three principal stresses at a point for any given loading and the stress at the tensile yield point, respectively.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

36


36

Engineering Materials

A typical example of plastic flow is the indentation test where a spherical ball is pressed in a semi-infinite body where $2a$ is the indentation diameter.

In a simplified model we may write that

if $\frac{P}{\pi a^2} > p_m$ plastic flow occurs



where, p_m is the flow pressure. This is also shown in figure.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

37

37

Engineering Materials

(c) Hardness

Property of the material that enables it to resist permanent deformation, penetration, indentation etc.

Size of indentations by various types of indenters are the measure of hardness

e.g. Brinell hardness test,

Rockwell hardness test,

Vickers hardness (diamond pyramid) test.

These tests give hardness numbers which are related to yield pressure (MPa).

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

38

38

Engineering Materials

(d) Ductility

This is the property of the material that enables it to be drawn out or elongated to an appreciable extent before rupture occurs.

The percentage elongation or percentage reduction in area before rupture of a test specimen is the measure of ductility.

Normally if percentage elongation exceeds 15% the material is ductile and

if it is less than 5% the material is brittle.

Lead, copper, aluminium, mild steel

are typical ductile materials.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

39

39

Engineering Materials

(e) Malleability

It is a special case of ductility where it can be rolled into thin sheets but it is not necessary to be so strong.

Lead,

Soft steel,

Wrought iron,

Copper and

Aluminium are some materials in order of diminishing malleability.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

40

40

Engineering Materials

(f) Brittleness

This is opposite to ductility.

Brittle materials show little deformation before fracture and failure occur suddenly without any warning.

Normally if the elongation is less than 5% the material is considered to be brittle.

E.g. cast iron, glass, ceramics

are typical brittle materials.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

41

41

Engineering Materials

(g) Resilience

This is the property of the material that enables it to resist shock and impact by storing energy.

The measure of resilience is the strain energy absorbed per unit volume.

For a rod of length L subjected to tensile load P , a linear load-deflection plot is shown in figure.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore


42

42

Engineering Materials

$$\text{Strain energy (energy stored)} = \frac{1}{2} P \delta L = \frac{1}{2} \frac{P}{A} \frac{\delta L}{L} AL = \frac{1}{2} \sigma \epsilon V$$

$$\text{Strain energy/unit volume} = \frac{1}{2} \sigma \epsilon$$



A linear load-deflection plot.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

43

43

Engineering Materials

(h) Toughness

This is the property which enables a material to be twisted, bent or stretched under impact load or high stress before rupture.

It may be considered to be the ability of the material to absorb energy in the plastic zone.

The measure of toughness is the amount of energy absorbed after being stressed upto the point of fracture.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

44

44

Engineering Materials

(i) Creep

When a member is subjected to a constant load over a long period of time it undergoes a slow permanent deformation, and this is termed as “creep”.

This is dependent on temperature.

Usually at elevated temperatures creep is high.

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

45

45

References

ABDULLA SHARIF, Design of Machine Elements, Dhanpat Rai Publications (P) Ltd, New Delhi, 1995.

V. B. Bhandari, Design of Machine Elements, Third Ed., The McGraw-Hills Companies, New Delhi

R. S. KHURMI and J.K.GUPTA, A Textbook of Machine Design, S.Chand and company Ltd., New Delhi, 2000.

<http://www.nptel.iitm.ac.in>

2/4/2026

Vijay Kumar Karma, IET, DAVV, Indore

46

46